

**BATTERY STRAPPING TOOL WITH FRICTION WELD SEAL FOR (PET / PP)**  
**DIGITAL CONTROL - FLAT AND ROUND SURFACES**

**TECHNICAL DATA :**

Compact, versatile and easy to use battery powered strapping tool equipped with two Li-ion Batteries and one Charger. Manual, semi-automatic or automatic operation. Bosch brushless high torque motor for less wear and long life. High speed take-up. Standard and (soft) low tension mode. High impact reinforced casing with metal nose for drop damage resistance. Reinforced circuit board located in front of battery for improved protection. Perfect balance enhances vertical or horizontal use and reduced operator fatigue.

Strap Width	3/8", 1/2" or 5/8" (10mm,13mm or 16mm)
Strap Thickness	.020" to .040"
Tension (Automatic Mode)	Min. 112 - 385 lbf. (500n-1712n)
High Speed Take Up	49' min. (15 mt/min)
Weight	8 lb. Including battery
Dimensions	6" H, 14" L, 4.5" W
Joint Type	Friction Weld Seal
Battery	AKKU Power 14.4 V, 3.0 Ah Li-ion
Order Code: MT 320-S / supersoft	155.990.832
Package Type (Surface)	Flat 5" Min. (120mm) - Round 28" Min. (700mm)



Also available in High Visibility Orange

MAILLIS STRAPPING SYSTEMS—USA Inc. 404 Wall Street, Fountain Inn, SC 29644

Phone: 877-962-4648 / Fax: 864-409-0367 / Web: [maillistrapping.com](http://maillistrapping.com) / E-mail: [info@maillistrapping.com](mailto:info@maillistrapping.com)

rev. 05/2015