

**BATTERY STRAPPING TOOL WITH FRICTION WELD SEAL FOR (PET / PP)
 DIGITAL CONTROL - FLAT AND ROUND SURFACES**
TECHNICAL DATA :

Compact, versatile, light weight and easy to use battery powered strapping tool equipped with two Li-ion Batteries and one Charger. Bosch brushless motor for less wear and long life. High speed take-up. Manual and Soft (low) tension mode. High impact reinforced casing with metal nose for drop damage resistance. Reinforced circuit board located in front of battery for improved protection. Perfect balance enhances vertical or horizontal use and reduced operator fatigue.

Strap Width	3/8", 1/2" or 5/8"
Strap Thickness	.020" to .040"
Tension	55 lbf. Min. - 370 lbf. Max.
High Speed Take Up	45' / min.
Weight	7.9 lbs. Including battery
Dimensions	6" H, 14" L, 4.5" W
Joint Type	Friction Weld Seal
Battery	AKKU Power 14.0 V, 1.5 Ah Li-ion (AKKU Battery Charger)
Order Code: MT 40	159990812 (Color is Orange)
Package Type (Surface)	Flat 5" min. (120mm) - Round 28" min. (700mm)



Manufactured by the M.J. Maillis Group

MAILLIS STRAPPING SYSTEMS—USA Inc. 404 Wall Street, Fountain Inn, SC 29644

Phone: 877-962-4648 / Fax: 864-409-0367 / Web: maillisstrapping.com / E-mail: info@maillisstrapping.com

rev. 03/2016