

**BATTERY STRAPPING TOOL WITH FRICTION WELD SEAL FOR (PET / PP)  
DIGITAL CONTROL - FLAT AND ROUND SURFACES**

**TECHNICAL DATA :**

Compact, versatile and easy to use battery powered strapping tool equipped with two Li-ion Batteries and one Charger. Manual, semi-automatic or automatic operation. Bosch brushless high torque motor for less wear and long life. High speed take-up. Standard and (soft) low tension mode. High impact reinforced casing with metal nose for drop damage resistance. Reinforced circuit board located in front of battery for improved protection. Perfect balance enhances vertical or horizontal use and reduced operator fatigue.

Strap Width	5/8"(16mm) - 3/4"(19mm) - 1" *.040 (25mm)
Strap Thickness	0.030" to 0.050" (1" x .040)
Tension	Min. 225 lbf. - 1,000 lbf. Max. (1000-4500 N)
High Speed Take Up	29.5' / min. (9mt / min)
Weight	8.8 Lb. Including battery
Dimensions	6" H, 14" L, 4.5" W
Joint Type	Friction Weld Seal
Battery	AKKU Power 18.0 V, 5.0 Ah Li-ion
Order Code: MT 450	156.990.812 (When ordering - Indicate Orange color if desired)
Package Type	Flat 5" min. dia. (120 mm) - Round 28" dia. (700 mm)

Also available in High Visibility Orange



Manufactured by the M.J. Maillis Group